



Highly Flexible CSA / UL 1696 PA 12 Conduit

Model: **0236.209.023**

Highly flexible, medium wall, high alternate bending strength for frequent reverse bending, high flex continuous motion applications, highly self-extinguishing, flame retardant, high UV resistance, free of silicone, cadmium, halogen, resistant to acids, solvents, oils. ASTM E-162, ASTM E-662, ASTM E-1354, SMP 800-C

Product Details

| | |
|---------------------|----------------|
| Manufacture Series | ROHRflex PA 12 |
| Color | Orange |
| Trade Size (in) | 3/4" |
| NW | 23 |
| Size (mm) | 28.5 |
| Profile | fine |
| ID (mm) | 23.0 |
| OD (mm) | 28.5 |
| BR stat. (mm) | 45.0 |
| BR dyn. (mm) | 100.000 |
| BR stat. (in) | 1.77 |
| BR dyn. (in) | 3.937 |
| Temp MIN °C | -50 |
| Temp MAX °C | 100 |
| Temp Short Term °C | 150 |
| Temp MIN °F | -58 |
| Temp MAX °F | 212 |
| Temp Short Term °F | 302 |
| Material | PA12 |
| Flammability | UL94-V2 |
| IP Rating | IP68 |
| Suitable Connectors | FlexaQuick |



800.633.6339
www.lapptannehill.com



"Unsurpassed in Cable Protection and Strain Relief"