

Carolprene® Type SVO

90°C, 300 Volt, UL/CSA Portable Cord

Product Construction:

Conductors:

- 18 AWG fully annealed stranded bare copper

Insulation:

- Premium-grade, color-coded 90°C EPDM
- Color code: See chart below

Jacket:

- Carolprene®, black
- Temperature range: -20°C to +90°C

Jacket Marking:

- CAROL (SIZE) (mm²) TYPE SVO 90°C (UL) --- CSA TYPE SVO FT2 300 VOLT ROHS MADE IN USA

Applications:

- Vacuum cleaners
- Light-duty equipment
- Office equipment

Features:

- Maintains flexibility in cold temperatures
- Resistant to oil and moisture
- Good tensile strength, elongation and aging characteristics
- Excellent flex life
- Ozone-, sunlight (UV)- and weather-resistant

Industry Approvals:

- UL Flexible Cord - UL 62
- CSA Flexible Cord - C22.2-49
- RoHS Compliant

Packaging:

- 250' (76.2 m)
- Other sizes and put-ups available on special order
- 4C cables available as UL recognized AWM as special order



TYPE SVO – 300 VOLT – UL/CSA

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOMINAL INS. THICKNESS		NOMINAL O.D.		CURRENT AMPS†	APPROX. NET WT. LBS/M ^(S)	STD. CTN.
				INCHES	mm	INCHES	mm			
13002	2	18	41/34	0.015	0.38	0.225	5.72	10	34	1000'
13003	3	18	41/34	0.015	0.38	0.235	5.97	10	40	1000'

† Green conductor for grounding only. Ampacities based on NEC Table 400.5(A)(1).
 (S) Actual shipping weight may vary.



800.633.6339

www.lapptannehill.com

COLOR CODE CHART

NO. OF CONDUCTORS	COLOR
2	Black, White
3	Black, White, Green

