

## UL 1422



**Construction: Conductors:** Silver plated copper. **Insulation:** Kynar.



Use to make solderless connections of wires to terminals.



**Features:**

- High temperature resistant
- Superior mechanical properties
- Economical price

**Technical Data:**

- ☒ **Temperature:** 105°C
- ⚡ **Rated Voltage:** No Voltage Rating
- 🎨 **Color Code:** Replace the X  
0-Black, 1-Brown, 2-Red,  
3-Orange, 4-Yellow, 5-Green,  
6-Blue, 7-Violet, 8-Gray, 9-White,  
54-Green/Yellow
- ☑ **Approvals:**  
UL 1422

Part Number	AWG	Stranding	Insulation Thickness (mils)	Nominal Outer Diameter Inches
1422-30-X	30	Solid	5	.021
1422-28-X	28	Solid	5	.024
1422-26-X	26	Solid	5	.027
1422-24-X	24	Solid	5	.031
1422-22-X	22	Solid	5	.036

## UL 1423



**Construction: Conductors:** Silver plated copper. **Insulation:** Kynar.



Use to make solderless connections of wires to terminals.



**Features:**

- High temperature resistant
- Superior mechanical properties
- Economical price

**Technical Data:**

- ☒ **Temperature:** 105°C
- ⚡ **Rated Voltage:**
- 🎨 **Color Code:** Replace the X  
0-Black, 1-Brown, 2-Red,  
3-Orange, 4-Yellow, 5-Green,  
6-Blue, 7-Violet, 8-Gray, 9-White,  
54-Green/Yellow
- ☑ **Approvals:**  
UL 1422

Part Number	AWG	Stranding	Insulation Thickness (mils)	Nominal Outer Diameter Inches
1423-30-X	30	Solid	4	.0195
1423-28-X	28	Solid	4	.0230
1423-26-X	26	Solid	4	.0260
1423-24-X	24	Solid	4	.0300
1423-22-X	22	Solid	4	.0350