

## UL STYLE 1061

CSA AWM I A/B (S-R PVC)

HOOK-UP WIRE / APPLIANCE WIRE



**CONDUCTORS:** • 26 AWG - 16 AWG Stranded Tinned Copper per ASTM B-33

**INSULATION:** • Color-Coded Semi-Rigid Polyvinyl Chloride (S-R PVC)

**TEMPERATURE RANGE/  
VOLTAGE RATING:** • UL 1061: 80°C/300V  
• CSM AWM I A/B: 80°C/300V  
• MIL-W-16878/1 Type B: 105°C/600V

**FLAME COMPLIANCES:** • UL VW-1  
• CSA FT-1

**INDUSTRY APPROVALS:** • UL Standard 758 - Style 1061  
• CSA AWM I A/B  
• MIL-W-16878/1 TYPE B

**STANDARD COLORS:** • Black • Orange • Blue • Violet  
• White • Yellow • Brown • Green/Yellow  
• Red • Green • Gray

**OPTIONS:** • Stripes available upon request (minimums may apply)  
• Other copper constructions available upon request (minimums may apply)

Gauge	Stranding	Nominal Wall		Nominal OD		Weight	
		in.	mm.	in.	mm.	lbs./mft	kg/km
26	7/34	0.009	0.23	0.038	0.97	1.4	2
24	7/.0076	0.009	0.23	0.045	1.14	2.9	4
22	7/.0096	0.009	0.23	0.051	1.30	2.8	4
20	10/30	0.009	0.23	0.058	1.47	4.0	6
18	16/30	0.009	0.23	0.067	1.70	6.1	9
16	26/30	0.009	0.23	0.078	1.98	9.3	14

Dimensions and weights are nominal and are subject to industry tolerances unless otherwise noted.

See page 127 for Ordering and Color Code information.



www.lapptannehill.com  
sales@lapptannehill.com  
800.633.6339



**Coleman Cable Inc.**  
800.323.9355 • www.colemancable.com