

## RJ45 CAT.6A Industry 10G connectors



### Application advantage

- Suitable for solid and stranded conductors
- Nickel-plated brass housing
- Supports 10 Gigabit Ethernet
- Provides IP68 protection
- Conforms to IEC 60603-7-51

### Approvals



Part number	Color code	Description	Conductor size		Cable outer diameter		Pack size
			stranded	solid	in	mm	
<b>Plug</b>							
21700630	T568A	inclusive RJ45 connector plug	27 - 22 AWG (7 wire)	26 - 22 AWG	0.197 - 0.355	5 - 9	1
21700631	—	dust cap	—	—	—	—	10
<b>Receptacle</b>							
21700632	T568B	inclusive RJ45 connector receptacle	27 - 22 AWG (7 wire)	26 - 22 AWG	0.197 - 0.355	5 - 9	1
21700633	—	dust cap	—	—	—	—	10

## RJ45 90° CAT.5e



### Application advantage

- Die-cast zinc housing
- Suitable for PROFINET® applications
- Suitable for solid and stranded conductors

### Approvals



Part number	Conductor size		Cable outer diameter		Pack size
	stranded	solid	in	mm	
21700638	27 - 22 AWG (7 wire)	24 - 22 AWG	0.217 - 0.394	5.5 - 10	1

## RJ45 90° CAT.6A



### Application advantage

- Die-cast zinc housing
- Suitable for PROFINET® applications
- Suitable for solid and stranded conductors

### Approvals



Part number	Color code	Conductor size		Cable outer diameter		Pack size
		stranded	solid	in	mm	
21700636	T568A	27 - 22 AWG (7 wire)	24 - 22 AWG	0.217 - 0.394	5.5 - 10.0	1
21700639	T568A	26 AWG (19 wire)	26 - 24 AWG	0.217 - 0.394	5.5 - 10.0	1
21700637	T568B	27 - 22 AWG (7 wire)	24 - 22 AWG	0.217 - 0.394	5.5 - 10.0	1
21700640	T568B	26 AWG (19 wire)	26 - 24 AWG	0.217 - 0.394	5.5 - 10.0	1

PROFINET® is a registered trademark of the PNO (PROFIBUS User Organization).  
 If not otherwise specified, all values relating to the product are nominal values.  
 Photographs are not to scale and are not true representations of the products in question.