

# ETHERLINE® TRAY CAT.7; stationary

## Tray-rated industrial Ethernet cable for stationary applications

LAPP KABEL STUTTGART ETHERLINE® TRAY CAT.7



ETHERLINE® TRAY CAT.7 is designed for stationary applications with performance and maximum transfer rate (IEEE 802.3) of 10 GBit/s up to 328 feet. Pairs are individually foil shielded with and overall braid shield; offering excellent shielding properties based on IEC 61156-5 and can be used in areas where reliable transmission is key including EtherNet/IP, Profinet with 4 pairs, EtherCAT, Power over Ethernet (IEEE 802.3af) and Power over Ethernet Plus (802.3at).

### Construction

- Conductors:** solid strand bare copper
- Pairs:** 4 twisted pairs individually shielded
- Insulation:** foam polyethylene insulation
- Shielding:** overall tinned copper braid
- Jacket:** Specially formulated PVC; green

### Recommended applications

Stationary applications, cable trays, industrial machinery, commercial and plant infrastructure

### Application advantage

- Wide application range due to multiple certifications
- PLTC (Power Limited Tray Cable) for use in cable trays
- Suitable for EtherNet/IP applications
- Suitable for PoE per IEEE 802.3af and 802.3at
- Sunlight resistant
- Meets or exceeds requirements for Cat.6A per ANSI/TIA 586.2-D

### Approvals



Cable attributes		page 648	
OIL	OR-03	FLAME	FR-03
MOTION	FL-01	MECH.	MP-02

Complete the installation	
SKINTOP® MS-SC page 522	RJ45 CAT.6A connectors page 258

ÖLFLEX® CONNECT solution	
ÖLFLEX® CONNECT CABLES page 605	

### Technical data

<p> <b>Minimum bend radius:</b> - for stationary use: 10 x cable diameter - for flexible use: 15 x cable diameter</p> <p> <b>Temperature range:</b> - for stationary use: -40°C to +80°C - for flexible use: -20°C to +80°C</p> <p> <b>Nominal voltage:</b> (not for power applications) UL/CSA 300V UL/CSA AWM 600V</p> <p> <b>Test voltage:</b> 1500V</p>	<p> <b>Characteristic impedance:</b> 100Ω ± 15Ω (1 - 100 MHz)</p> <p> <b>Color code:</b> white/blue &amp; blue, white/orange &amp; orange, white/green &amp; green, white/brown &amp; brown</p> <p> <b>Approvals:</b> UL: CMG per UL 444 PLTC per UL 13 AWM 21695 per UL 758 Canada: c(UL) CMG per CSA C22.2 No. 214 Additional: cRU AWM II A/B FT4 per CSA C22.2 No 210</p>
---	--

Part number	Construction	Stranding	Jacket material	Jacket color	Approvals	PoE	Nominal outer diameter		Approx. weight	RJ45 Connector
						in mm		lbs/mft		
<b>CAT.7</b>										
2170472	22 AWG/4pr	solid	PVC	green	UL CMG, UL AWM 600V, PLTC	yes	0.350	8.9	77	21700636

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question.