


SKINTOP® CLICK/CLICK-R

Strain relief with quick "click" insertion system



Complete the installation



SKINTOP®
DIX bushing
page 545



Plugs
page 522



Removal tool

SKINTOP® CLICK is an innovative cable insertion system that provides fast, highly flexible assembly. Easy snap-in-place installation results in fixed, centered, strain relief with maximum protection in seconds. Mounting hole is based on metric thread. SKINTOP® CLICK-R includes reducer bushing.

Recommended applications

Applications where locknut installation is difficult to reach or to secure, such as dual wall enclosures and temperature controlled assemblies where insulation is used

Approvals



1 removal tool included per pack.
Additional tools are available; see table for part numbers.

Accessories

Application advantage

- Up to 70% installation time savings due to innovative CLICK system
- Ideal for hard-to-reach dual wall enclosures and limited access spaces
- Reduced inventory as no locknuts are required
- The heavy duty SKINTOP® design provides great pullout strength and very reliable strain relief
- Superior integrated locking mechanism includes an internal ratchet for vibration-proof protection

Technical data

Material:

- body: special polyamide
- seal: special elastomer

Temperature range:

- static: -40 °C to +100 °C
- dynamic: -20 °C to +100 °C

Color:

black (RAL 9005), UV resistant
gray (RAL 7001)

IP Protection:

- M12: IP68, 4 bar
- M16 - M25: IP68, 5 bar
- M32: IP68, 1 bar

Part number*	Mounting hole size	UL status	Clamping range (øF)		Wrenching flats (SW1/SW2)	Overall length (C)	Thread length (D)	Hole (øM)	Pack size	Removal tool	
			in	mm							
Standard											
53112923	53112921	M12	Recognized	0.177-0.276	4.5-7	0.591/0.709	1.576	0.315	0.484 (-.008)	50	53112696
53112882	53112876	M16	Recognized	0.197-0.394	5-9	0.748/0.866	1.654	0.315	0.642 (-.008)	50	53112697
53112883	53112877	M20	Listed	0.276-0.512	7-13	0.985/1.063	1.792	0.315	0.799 (-.008)	25	53112698
53112884	53112878	M25	Listed	0.354-0.669	9-17	1.182/1.339	1.910	0.315	0.996 (-.008)	25	53112699
53112924	53112922	M32	Listed	0.433-0.787	11-20	1.417/1.576	2.167	0.315	1.272 (-.008)	25	53112797
Reducer bushing											
53112929	53112927	M12	Recognized	0.1385-0.197	3.5-5	0.591/0.709	1.576	0.315	0.484 (-.008)	50	53112696
53112885	53112879	M16	Recognized	0.157-0.276	4-7	0.748/0.866	1.654	0.315	0.642 (-.008)	50	53112697
53112886	53112880	M20	Listed	0.197-0.394	5-10	0.985/1.063	1.792	0.315	0.799 (-.008)	25	53112698
53112887	53112881	M25	Listed	0.236-0.512	6-13	1.182/1.339	1.910	0.315	0.996 (-.008)	25	53112699
53112931	53112928	M32	Listed	0.276-0.591	7-15	1.417/1.576	2.167	0.315	1.272 (-.008)	25	53112797

* Suitable for wall thickness of 1 - 4 mm (0.039 - 0.157 in)