



SKINDICHT® SM-M



Application range

- Used when a gland has to be countered, or in through-holes on thin-walled housings

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Technical data



Classification ETIM 5/6

ETIM 5.0/6.0 Class-ID: EC000940

ETIM 5.0/6.0 Class-Description:

Locknut for cable screw gland



Material

Nickel-plated brass



Temperature range

-60°C to +200°C

Article number	Article designation / size	Thickness (mm)	SW wrench size mm	Outer Ø (mm)	Pieces / PU
SKINDICHT® SM-M					
52102998	M 6 x 1	3.2	10	11.1	100
52102997	M 8 x 1	4.0	13	14.4	100
52102999	M 10 x 1	5.0	17	19.1	100
52103000	M 12 x 1,5	3.0	15	16.5	100
52103010	M 16 x 1,5	3.0	19	20.9	100
52103020	M 20 x 1,5	3.5	24	26.4	100
52103030	M 25 x 1,5	4.0	30	33.0	100
52103040	M 32 x 1,5	4.0	36	39.6	100
52103050	M 40 x 1,5	5.0	46	50.6	50
52103060	M 50 x 1,5	5.0	60	65.0	50
52103070	M 63 x 1,5	5.0	70	77.0	25
52103071	M 75 x 1,5	8.0	85	95.0	1
52103072	M 90 x 2	10.0	102	114.0	1
52103073	M 110 x 2	12.0	124	135.0	1
SKINDICHT® SM-M - Lead-free brass version					
52103000LF	M 12 x 1,5	3.0	15	16.5	100
52103010LF	M 16 x 1,5	3.0	19	20.9	100
52103020LF	M 20 x 1,5	3.5	24	26.4	100
52103030LF	M 25 x 1,5	4.0	30	33.0	100
52103040LF	M 32 x 1,5	4.0	36	39.6	100
52103050LF	M 40 x 1,5	5.0	46	50.6	50
52103060LF	M 50 x 1,5	5.0	60	65.0	50
52103070LF	M 63 x 1,5	5.0	70	77.0	25

Photographs and graphics are not to scale and do not represent detailed images of the respective products.