

## SECURITY ALARM CABLE

### UNSHIELDED

CMP/FT6 Rated, FPLP, CL2P, CL3P



### RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

PART NO.	AWG/ COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		SHIP WT / 1M'
			INCH	mm	INCH	mm	
<b>22 AWG</b>							
982202	22/2	SOL	.018	.457	.118	3.00	9
912202	22/2	7	.018	.457	.124	3.15	10
912203	22/3	7	.018	.457	.131	3.33	13
982204	22/4	SOL	.018	.457	.136	3.45	16
912204	22/4	7	.018	.457	.143	3.63	17
912206	22/6	7	.018	.457	.171	4.34	24
912208	22/8	7	.018	.457	.186	4.72	31
912210	22/10	7	.018	.457	.193	4.90	40
912212	22/12	7	.018	.457	.225	5.72	49
<b>20 AWG</b>							
912002	20/2	7	.018	.457	.138	3.51	14
912004	20/4	7	.018	.457	.160	4.06	24
<b>18 AWG</b>							
911802	18/2	7	.018	.457	.157	3.99	18
911803	18/3	7	.018	.457	.168	4.27	25
911804	18/4	7	.018	.457	.186	4.72	36
911805	18/5	7	.018	.457	.203	5.16	41
911806	18/6	7	.018	.457	.222	5.64	51
911808	18/8	7	.018	.457	.242	6.15	65
911809	18/9	7	.018	.457	.262	6.65	68
911810	18/10	7	.018	.457	.286	7.26	75
911812	18/12	7	.018	.457	.296	7.52	84
<b>16 AWG</b>							
911602	16/2	19	.018	.457	.180	4.57	26
911603	16/3	19	.018	.457	.191	4.85	38
911604	16/4	19	.018	.457	.211	5.36	52
<b>14 AWG</b>							
911402	14/2	19	.018	.457	.222	5.64	40
911403	14/3	19	.018	.457	.236	5.99	60
911404	14/4	19	.018	.457	.261	6.63	73
<b>12 AWG</b>							
911202	12/2	19	.018	.457	.272	6.91	58
911204	12/4	19	.018	.457	.308	7.82	111

### PRODUCT DESCRIPTION

Low smoke PVC insulated stranded bare copper conductors, twisted with an overall low smoke white PVC jacket\* with rip cord.

\*Other colors available upon request. Please consult factory for minimums and lead times.

### SPECIFICATIONS

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	Low Smoke PVC
22 AWG	.007" PVC
20 AWG	.008" PVC
18 AWG	.009" PVC
16 AWG	.010" PVC
14-12 AWG	.012" PVC
<b>Jacket</b>	Low Smoke PVC
<b>NEC Articles</b>	
22-16 AWG:	FPLP/760, CMP/800, CL3P, CL2P/725
14-12 AWG:	FPLP, CL3P
<b>Voltage Rating</b>	300 V
<b>Temp. Rating</b>	75°C

### APPLICATIONS

- Security Systems
- Intercom Systems
- Sound/Audio System
- Power-Limited Controls

### COLOR CODE CHART

Cond	Color	Cond	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

### AVAILABLE PUT-UPS

1,000' Reels and Boxes  
 500' Reels and Boxes  
 Other lengths available. Please consult your factory representative for availability.

### CABLE IDENTIFICATION

XX AWG XC (ETL)us TYPE CL3P/FPLP c(ETL)us TYPE CMP 3054355

\*14-12 AWG are not recognized by c(UL) or c(ETL).

